

PORTABLE pH METER CODE 0430-HA21

**INSPECTION
CERTIFICATE**

- 1~3 points automatic calibration, with calibration guidance and automatic inspection function
- Manual and automatic temperature compensation functions for more accurate measurement
- The meter provides three types of reading stability criteria
- 50 sets of data storage
- Featuring a foldable stand, suitable for multi scenario applications
- Probe protection level: IP57



plastic pH electrode
(included)



calibration solution (included)



hydrofluoric acid/strong acid resistant
glass pH electrode unit (optional)

SPECIFICATION

pH	range	0.00~14.00pH
	resolution	0.1/0.01pH
	accuracy*	± (0.01pH+1d)
	temperature compensation	0°C~100°C (manual or automatic)
	calibration mode	1~3 points
mV	range	-1000mV~+1000mV
	resolution	1mV
	accuracy*	± (0.2%FS+1d)
Temperature	range	0°C~100°C
	resolution	0.1°C
	accuracy*	± (0.5°C+1d)
Calibration point		USA (4.00, 7.00, 10.01) NIST (4.01, 6.86, 9.18)
Power supply		3×1.5V AA batteries
Dimension (L×W×H)		86×196×33mm
Net weight		292g

*d is the resolution

STANDARD DELIVERY

Main unit	1 pc
Calibration solution	3 bottles (USA)
1.5V AA battery	3 pcs
Plastic pH electrode	1 pc

OPTIONAL ACCESSORY

Hydrofluoric acid/strong acid resistant glass pH electrode	0430-HA21-833
Strong alkali/high salt/high temperature pH electrode	0430-HA21-843