

BRASS  
CONNECTION

BRASS  
BOURDON TUBE

PLASTIC  
CASE

PLASTIC  
WINDOW

- Plastic case, plastic window, brass connection, brass bourdon tube, with memory pointer
- Used for water test

#### Process connection

<b>C1</b>	G1/4 (Ø50mm, Ø63mm)
<b>C2</b>	R1/4 (Ø50mm, Ø63mm)
<b>C3</b>	NPT1/4 (Ø50mm, Ø63mm)

#### Dial size

<b>D1</b>	Ø50mm (2")
<b>D2</b>	Ø63mm (2.5")

#### Pressure range

<b>R1</b>	(0~7bar/0~100psi)
<b>R2</b>	(0~11bar/0~160psi)
<b>R3</b>	(0~14bar/0~200psi)
<b>R4</b>	(0~20bar/0~300psi)



5210-C1D2R3

## WATER TEST PRESSURE GAUGES CODE 5210-□□□



#### Code example:

<b>5210-C1D2R3</b>	<b>C1</b> -connection thread G1/4
	<b>D2</b> -dial size Ø63mm
	<b>R3</b> -pressure range (0~14bar/0~200psi)

#### SPECIFICATION

<b>Accuracy class</b>	CL 2.5 for 50mm (2"); CL 1.6 for 63mm (2.5")
<b>End connection</b>	with 3/4" female thread copper alloy swivel connection
<b>Ambient temperature</b>	-20°C~60°C (-4°F~140°F)
<b>Medium temperature</b>	≤60°C (140°F)