GAS TEST PRESSURE GAUGES
CODE 5211-□□□□

ELECTROPLATING CASE | BRASS BOURDON TUBE | STAINLESS STEEL RING | BRASS CONNECTION | ELECTROPLATING BRASS MOUNT

- Electroplating case, stainless steel ring, brass connection, brass bourdon tube, electroplating brass mount
- Used for gas test

5211-C1D2W1R2

5211-C□D□W□R□
connection
dial size
window
pressure range

Process connection

C1	G1/4 (Ø50mm, Ø63mm)
C2	R1/4 (Ø50mm, Ø63mm)
C3	NPT1/4 (Ø50mm, Ø63mm)

Dial size

D1	Ø50mm (2")
D2	Ø63mm (2.5")

Windows

W1	plastic
W2	tempered glass

Pressure range

R1	(0~7bar/0~100psi)
R2	(0~10bar/0~140psi)
R3	(0~11bar/0~160psi)
R4	(0~14bar/0~200psi)
R5	(0~20bar/0~300psi)

Code example:

5211-C1D2W1R2	**C1-**connection thread G1/4
	D2-dial size Ø63mm
	W1-plastic material window
	R2-pressure range (0~10bar/0~140psi)

SPECIFICATION

Accuracy class	CL 2.5 for 50mm (2"); CL 1.6 for 63mm (2.5")
End connection	with 3/4NPT female mount
Ambient temperature	-20°C~60°C (-4°F~140°F)
Medium temperature	≤60°C (140°F)