

STAINLESS
STEEL CASE

STAINLESS STEEL
DIAPHRAGM

STAINLESS STEEL
RING

STAINLESS STEEL
CONNECTION

DIAPHRAGM PRESSURE GAUGES CODE 5215-□□□□



5215-C1D1W1R15

5215-C□D□W□R□
 connection ——— dial size ——— pressure range ——— window ———

- Stainless steel case, stainless steel ring, stainless steel connection, stainless steel diaphragm
- Used to measure micro pressure and negative pressure of gas that has no corrosion to stainless steel

Code example:

5215-C1D1W1R15	C1 -connection thread G1/4
	D1 -dial size Ø63mm
	W1 -tempered glass material window
	R15 -pressure range (0~250mbar/0~2500mmH ₂ O)

SPECIFICATION

Accuracy class	CL 1.6 for 63mm (2.5"), 100mm (4"); CL 1.0 for 160mm (6.3")
Connection position	bottom
Ambient temperature	-40°C~60°C (-40°F~140°F)
Medium temperature	≤60°C (140°F)

Process connection

C1	G1/4 (Ø63mm)
C2	R1/4 (Ø63mm)
C3	NPT1/4 (Ø63mm)
C4	G3/8 (Ø100mm, Ø160mm)
C5	R3/8 (Ø100mm, Ø160mm)
C6	NPT3/8 (Ø100mm, Ø160mm)
C7	G1/2 (Ø100mm, Ø160mm)
C8	R1/2 (Ø100mm, Ø160mm)
C9	NPT1/2 (Ø100mm, Ø160mm)

Dial size

D1	Ø63mm (2.5")
D2	Ø100mm (4")
D3	Ø160mm (6.3")

Window

W1	tempered glass
W2	safety glass

Pressure range

R1	(-600~0mbar/-6000~0mmH ₂ O)
R2	(-400~0mbar/-4000~0mmH ₂ O)
R3	(-250~0mbar/-2500~0mmH ₂ O)
R4	(-160~0mbar/-1600~0mmH ₂ O)
R5	(-100~0mbar/-1000~0mmH ₂ O)
R6	(-60~0mbar/-600~0mmH ₂ O)
R7	(-40~0mbar/-400~0mmH ₂ O)
R8	(-25~0mbar/-250~0mmH ₂ O)
R9	(-10~150mbar/-100~1500mmH ₂ O)
R10	(0~25mbar/0~250mmH ₂ O)
R11	(0~40mbar/0~400mmH ₂ O)
R12	(0~60mbar/0~600mmH ₂ O)
R13	(0~100mbar/0~1000mmH ₂ O)
R14	(0~160mbar/0~1600mmH ₂ O)
R15	(0~250mbar/0~2500mmH ₂ O)
R16	(0~400mbar/0~4000mmH ₂ O)
R17	(0~600mbar/0~6000mmH ₂ O)
R18	(0~700mbar/0~7000mmH ₂ O)