

## ARBITRARY WAVEFORM GENERATORS

- Maximum output frequency: 60MHz
- Maximum sampling rate: 300MSa/s
- 14 bits vertical resolution
- Output waveform: 5 standard waveforms, 45 built-in arbitrary waveforms
- Modulation: AM, FM, PM, FSK, PWM, ASK, PSK, sweep, burst



9535-1060

### SPECIFICATION

Code	9535-1010	9535-1025	9535-1050	9535-1060	
Channel	2				
Maximum output frequency	10MHz	25MHz	50MHz	60MHz	
Sampling rate	125MSa/s		300MSa/s		
Vertical resolution	14bits				
Output waveform	standard waveform	sine, square, ramp, pulse, noise			
	arbitrary waveform	exponential rise/fall, sin(x)/x, step wave, and others total 45 built-in waveforms			
Arbitrary waveform length	2~8K	2~10K			
Output mode	continuous, modulation, frequency sweep, pulse burst				
Modulation type	AM, FM, PM, FSK, PWM, ASK, PSK				
Frequency characteristic	sine	1μHz~10MHz	1μHz~25MHz	1μHz~50MHz	1μHz~60MHz
	square	1μHz~5MHz		1μHz~25MHz	1μHz~30MHz
	ramp	1μHz~1MHz			
	pulse	1μHz~5MHz		1μHz~10MHz	1μHz~15MHz
	noise (-3dB)	25MHz (gaussian white noise)			
	arbitrary waveform	1μHz~10MHz			
	resolution	1μHz~7bits			
Amplitude characteristic	output amplitude	high resistance: 1mVpp~20Vpp (≤25MHz), 1mVpp~10Vpp (≤60MHz)			50Ω: 1mVpp~10Vpp (≤25MHz), 1mVpp~5Vpp (≤60MHz)
	amplitude accuracy	1mVpp~4bits			
	offset range (AC+DC)	high resistance: ±10V, 50Ω: ±5V			
	offset resolution	1mVpp			
Frequency counter	output impedance	50Ω			
	measurement function	frequency, period, positive/negative pulse width, duty cycle			
	frequency range	100mHz~200MHz			
	frequency resolution	6bits			
Power supply	AC 110V/220V, 50/60Hz				
Dimension (L*W*H)	295*235*110mm				
Net weight	3kg				

### STANDARD DELIVERY

Main unit	1 pc
BNC test clip	1 pc
USB cable	1 pc

### POWER AMPLIFIER MODULE SPECIFICATION (OPTIONAL)

Full power bandwidth	DC~100kHz
Gain	X10
Maximum output power	10W
Maximum output voltage	22Vpp

### OPTIONAL DELIVERY

Power amplifier module	9535-PA (must be installed in factory)
------------------------	--