

ATTENTION: CLOCKWISE  
OPERATION ONLY

- Ratchet head
- Torque is preset, to prevent adjustment by mistake during use
- The torque is set at the factory before delivery. Customers can also set the torque with torque adjustment tool (**optional**) and digital torque testers (**IST-TT□□□, optional**)
- Clockwise operation only



torque adjustment tool  
(optional)



IST-PW125

## SPECIFICATION

Code	Adjustable range *		Accuracy	Square driver (D)	Length	Weight
IST-PW5	1~5N.m	10~45lb.in	±3%	1/4"	162mm	250g
IST-PW10	2~10N.m	20~90lb.in		1/4"	173mm	260g
IST-PW12	2.5~12N.m	20~105lb.in		1/4"	184mm	450g
IST-PW20	4~20N.m	30~180lb.in		1/4"	184mm	450g
IST-PW30	6~30N.m	50~250lb.in		3/8"	214mm	500g
IST-PW60	10~60N.m	9.0~45lb.ft		3/8"	255mm	560g
IST-PW125	25~125N.m	20~90lb.ft		3/8"	366mm	790g
IST-PW200	40~200N.m	30~150lb.ft		1/2"	457mm	1200g
IST-PW340	65~340N.m	50~250lb.ft		1/2"	691mm	1960g
IST-PW500	100~500N.m	80~400lb.ft		3/4"	915mm	2800g
IST-PW650	150~650N.m	100~500lb.ft		3/4"	915mm	2800g
IST-PW800	160~800N.m	120~600lb.ft	3/4"	1030mm	5000g	
IST-PW1000A	200~1000N.m	150~750lb.ft	±3% (≤500N.m) ±4% (>500N.m)	3/4"	1260mm	6000g
IST-PW1000B	200~1000N.m	150~750lb.ft		1"	1260mm	6000g
IST-PW1500	300~1500N.m	200~1100lb.ft	1"	1610mm	8000g	
IST-PW2000	400~2000N.m	300~1500lb.ft	1"	1910mm	9500g	
IST-PW3000	600~3000N.m	400~2200lb.ft	±4%	1"	2010mm	9900g

## OPTIONAL ACCESSORY

Torque adjustment tool	IST-36WM-TOOL1 (suitable for IST-PW5, IST-PW10)
	IST-PW-TOOL (suitable for all codes except IST-PW5, IST-PW10)

\* Adjust to a fixed torque value according to customer requirements before delivery