

BUILT-IN WIRELESS ULTRASONIC THICKNESS GAUGE (ADVANCED TYPE) CODE ISU-800DWL

- Real-time temperature compensation eliminates the error caused by temperature variation
- Support both single element transducers and dual element transducers
- Measure the thickness of substrate through coating
- Measuring mode: standard mode (dual element transducer: P-E mode, single element transducer: I-E mode), penetrate coating mode (dual element transducer: I-E mode, single element transducer: E-E mode or auto mode)
- Measure method: single point, scanning, deviation
- Set upper and lower limits for alarm when out-of-tolerance
- Single point and 2 points calibration
- Keyboard lock function avoids parameter setting change caused by unintended press during measurement
- Memory 1000 measurement values
- Data can be transmitted to PC by wireless connection or Mini-USB cable



PENETRATE COATING AND MEASURE THE THICKNESS OF SUBSTRATE

BUILT-IN WIRELESS

REAL-TIME TEMPERATURE COMPENSATION

DATA OUTPUT

transducer
ISU-S15-P06
(included)



receiver (optional)



transducer
ISU-S2M-P14
(optional)



transducer
ISU-G5M-P10
(optional)



transducer
ISU-G5M-P08
(optional)



transducer
ISU-G7M-P06
(optional)



transducer
ISU-G2M-P12
(optional)



transducer
ISU-H3M-P12
(optional)



delay block
ISU-S15-P06-CB
(optional)



delay block
ISU-S15-P06-CB1
(optional)



SPECIFICATION

Measuring range	refer to the specification of transducers
Resolution	0.01mm/0.001mm
Accuracy	refer to the specification of transducers
Data output	wireless and USB
Velocity	1~19999m/s
Power supply	3.7V rechargeable lithium battery
Dimensions	165×75×30mm
Net weight	260g

* On C45 carbon steel

STANDARD DELIVERY

Main unit	1 pc
Transducer ISU-S15-P06	1 pc
Power adaptor	1 pc
USB cable	1 pc
Couplant	1 bottle

OPTIONAL ACCESSORY

Transducer	refer to the specification of transducers
Couplant (for ISU-H3M-P12)	ISU-HT5-COUPPLANT
Thermal printer (with cable)	ISU-800D-PRINTER
Receiver	7315-2/3/6/7/8/9

SPECIFICATION OF TRANSDUCERS

Code	Type	Freq	Diameter (Ød)	Measuring range	Min. size of pipes (diameter × wall thickness)	Accuracy	Applicable temperature	Application
ISU-S15-P06 (included)	single element	15MHz	8mm	I-E: 0.9~28mm E-E: 0.15~14mm	Ø10×1.5mm Ø15×0.35mm	±0.02mm/0.3%H ^{**} (take the larger one)	-10°C~60°C	high precision or thin workpieces
ISU-S15-P06-CB (optional) ^{***}	—	—	5mm	I-E: 0.9~10mm E-E: 0.15~5mm	Ø10×1.2mm Ø15×0.35mm			high precision or irregular surface
ISU-S15-P06-CB1 (optional) ^{***}	—	—	8mm	I-E: 0.9~38mm E-E: 0.3~19mm	—			high precision or thick workpieces
ISU-S2M-P14 (optional)	single element	2MHz	19mm	I-E: 30~2000mm E-E: 30~1000mm	—	±0.5%H ^{**}	-10°C~310°C	ultra-thick workpieces
ISU-G5M-P10 (optional)	dual element	5MHz	13mm	0.8~300mm	Ø25×3mm	±0.04mm (range: <10mm) ±H/333mm ^{**} (range: ≥10mm)	-10°C~60°C	normal workpieces
ISU-G5M-P08 (optional)	dual element	5MHz	11mm	0.8~225mm	Ø20×1.2mm			curved surface and normal workpieces
ISU-G7M-P06 (optional)	dual element	7.5MHz	9mm	0.8~50mm	Ø15×1.2mm			curved surface and small workpieces
ISU-G2M-P12 (optional)	dual element	2MHz	17mm	3~700mm	Ø30×4mm	±0.05mm/0.5%H ^{**} (take the larger one)	-10°C~310°C	castings and thick workpieces
ISU-H3M-P12 (optional)	dual element	3MHz	15mm	2~200mm	Ø25×3mm	±0.05mm/0.5%H ^{**} (take the larger one)		workpieces with high temperature

^{**} H is the measured thickness in mm

^{***} Delay blocks, suitable for transducer **ISU-S15-P06**