PORTABLE pH METER **CODE 0430-HA21**

- 1~3 points automatic calibration, with calibration guidance and automatic inspection function
- Manual and automatic temperature compensation functions for more accurate measurement
- The meter provides three types of reading stability criteria
- 50 sets of data storage
- Featuring a foldable stand, suitable for multi scenario applications
- Probe protection level: IP57





standard solution (included)



hydrofluoric acid/strong acid resistant glass pH electrode unit (optional)

SPECIFICATION

SPECIFICATION STATE OF THE PROPERTY OF THE PRO		
рН	range	0.00~14.00pH
	resolution	0.1/0.01pH
	accuracy*	±(0.01pH+1d)
	temperature compensation	0°C~100°C (manual or automatic)
	calibration mode	1~3 points
mV	range	-1000mV~+1000mV
	resolution	1mV
	accuracy*	±(0.2%FS+1d)
Temperature	range	0°C~100°C
	resolution	0.1°C
	accuracy*	±(0.5°C+1d)
Standard solution		pH buffers: 4.00, 7.00, 10.01
Powers		3×1.5V AA batteries
Dimension		86×196×33mm
Weight		292g

^{*} d is the resolution

STANDARD DELIVERY

STANDARD DELIVERT		
Main unit	1 pc	
Standard solution	3 bottles	
1.5V AA battery	3 pcs	
Plastic pH electrode	1 pc	

OPTIONAL ACCESSORY

Hydrofluoric acid/strong acid resistant glass pH electrode	0430-HA21-A
Strong alkali/high salt/high temperature pH electrode	0430-HA21-B