

## **BLUETOOTH pH ELECTRODES**

- Suitable for water quality testing, sewage treatment, food and cosmetic testing
- Standard android software that can read electrode parameters
- Automatic temperature compensation
- Multiple parameters can be measured simultaneously
- Test records can be exported
- Low voltage alarm
- Built-in Bluetooth with a 10m transmission range (under unobstructed and interference-free conditions)
- Automatic power off



software (included), only available on Android



## **SPECIFICATION**

SPECIFICATION				
Code		0437 <b>-</b> HB31	0437 <b>-</b> HB32	
Material		plastic	glass	
Suitable applications		conventional water, weak acids, weak alkalis	strong acids, strong alkalis	
рН	measuring range	0.00~14.00pH		
	resolution	0.01pH		
	accuracy	±0.02pH		
	calibration mode	1~5 points		
Temperature	measuring range	0~99.9°C		
	resolution	0.1°C		
	accuracy	±0.5°C		
	compensation range	0~99.9°C		
Calibration point		NIST (4.01, 6.86, 9.18)		
		USA (4.00, 7.00, 10.01)		
Data storage		manual, automatic		
Power supply		rechargeable button battery (LIR2032 battery×1)		
Dimension (L×W×H)		210×25×25mm		
Weight		60g		

## STANDARD DELIVERY

Main unit	1 pc	
Standard solution	3 bottles (USA)	
LIR2032 battery	2 pcs	
USB cable	1 pc	
Charger	1 pc	