

DIGITAL OFFSET CALIPERS

DATA
OUTPUT



1186-150A

- Non waterproof
- The left jaw can slide up and down to facilitate measurement of stepped sections
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel

With data interface (optional data output cable: code 7315-25 receiver is needed, 7302-21)

(mm)

| Code | Range | Accuracy | L | a | b | c | d | e | f |
|-----------|---------------|----------|-----|----|------|----|-----|----|---|
| 1186-150A | 0-150mm/0-6" | ±0.04mm | 249 | 40 | 16.5 | 10 | 110 | 17 | 7 |
| 1186-200A | 0-200mm/0-8" | ±0.04mm | 299 | 50 | 19.5 | 10 | 120 | 17 | 7 |
| 1186-300A | 0-300mm/0-12" | ±0.05mm | 399 | 60 | 20.5 | 10 | 130 | 17 | 7 |

Built-in wireless (receiver code 7315-2/3/6/7/8/9 is needed)

(mm)

| Code | Range | Accuracy | L | a | b | c | d | e | f |
|-------------|---------------|----------|-----|----|------|----|-----|----|---|
| 1186-150AWL | 0-150mm/0-6" | ±0.04mm | 249 | 40 | 16.5 | 10 | 110 | 17 | 7 |
| 1186-200AWL | 0-200mm/0-8" | ±0.04mm | 299 | 50 | 19.5 | 10 | 120 | 17 | 7 |
| 1186-300AWL | 0-300mm/0-12" | ±0.05mm | 399 | 60 | 20.5 | 10 | 130 | 17 | 7 |

