



## **BALL SCREW PITCH CIRCLE DIAMETER COMPARATORS**

PROBE AND CALIBRATION PLUG GAUGE
NEED TO BE CUSTOMIZED ACCORDING TO THE WORKPIECE









2677-50

- Measuring the pitch circle diameter of ball screws
- Probe and calibration plug gauge need to be customized according to the workpiece

2677-20

Adjustable resolution: 0.0005mm/0.00002"

0.001mm/0.00005"

0.01mm/0.0005"

- Digital indicator uses absolute encoder, the original data remains after power off
- Digital indicator button function: data output, tolerance, data preset, data hold, measuring direction change, max./min./TIR, power off time, on/off, mm/inch, resolution adjustment
- Digital indicator uses rechargeable battery, for 24 hours continuous working
- Optional accessory: wireless transmitter(code **7315-60**, receiver is needed)

Code	Range	Contact point opening range	Effective stroke of anvil	Accuracy*	Repeatability
2677-20	6 <b>-</b> 20mm	6mm	0.1mm	0.005mm	0.001mm
2677-50	20 <b>-</b> 50mm	15mm	0.1mm	0.005mm	0.001mm

<sup>\*</sup>When under the effective stroke of the anvil, the accuracy can reach 0.005mm