

DIGITAL INTERNAL CHAMFER GAUGES





Unit: mm digital indicator digital indicator (included) (included) stainless steel holder stainless steel holder probe (TiN coated) probe (TiN coated) Ø41 Ø47 Ø21 2937-101 Α 2937-302 1**-**20mm 20-40mm

- Measure end diameter of chamfer or taper holes
- Resolution: 0.01mm/0.0005"
- Direct read (end diameter), no calculations
- TiN coated, wear/rust-resistant
- Optional accessory: wireless transmitter code 7315-51B (receiver is needed)

angle α=90°

Code	Measuring range(ØD)	Accuracy	Type	Setting ring(included)
2937-101	1 - 20mm	±0.02mm	Α	Ø10mm
2937-102	20 - 40mm	±0.02mm	В	Ø30mm


angle α=130°

Code	Measuring range(ØD)	Accuracy	Type	Setting ring(included)
2937-201	1 - 20mm	±0.02mm	Α	Ø10mm
2937-202	20 - 40mm	±0.02mm	В	Ø30mm

angle α=150°

angle α=150°							
Code	Measuring range(ØD)	Accuracy	Type	Setting ring(included)			
2937-301	1 - 20mm	±0.03mm	Α	Ø10mm			
2937-302	20 - 40mm	±0.03mm	В	Ø30mm			

measurement principle



measure end diameter of chamfer or taper holes

