




- Used with standard outside micrometers to measure pitch diameter of screw threads
- Diameter accuracy: ±0.5µm
- Cylindricity: 1µm
- Hardness: HRC60
- Supplied with manufacturer inspection certificate
- Scope of application: outside diameter of thread ≤50mm







For outside micrometers with spindle Ø6.35mm (ØD)

| Code | Pin gage diameter Applicable pitch | |
|------------------|---|----------------------|
| | | |
| 7382-11 | Ø0.170mm | 0.2mm, 0.25mm, 0.3mm |
| 7382-12 | Ø0.195mm | 0.35mm |
| 7382-13 | Ø0.220mm | 0.4mm |
| 7382-14 | Ø0.250mm | 0.45mm |
| 7382-15 | Ø0.290mm | 0.5mm |
| 7382-16 | Ø0.335mm | 0.6mm |
| 7382-17 | Ø0.390mm | 0.7mm |
| 7382-18 | Ø0.455mm | 0.75mm, 0.8mm |
| 7382-19 | Ø0.530mm | 0.9mm |
| 7382-110 | Ø0.620mm | 1.0mm |
| 7382-111 | Ø0.725mm | 1.25mm |
| 7382-112 | Ø0.895mm | 1.5mm |
| 7382-113 | Ø1.100mm | 1.75mm, 2.0mm |
| 7382-114 | Ø1.350mm | 2.5mm |
| 7382-115 | Ø1.650mm | 3.0mm |
| 7382-116 | Ø2.050mm | 3.5mm |
| 7382-117 | Ø2.550mm | 4mm, 4.5mm |
| 7382-118 | Ø3.200mm | 5mm, 5.5mm, 6mm |
| 7382 - 1S | 18 pairs/set, including all above 3-wires | |

For outside micrometers with spindle Ø6.50mm (ØD)

| O de la Piarre di acceptante de la contra del contra de la contra del la contra de la contra de la contra del la c | | |
|--|---|----------------------|
| Code | Pin gage diameter | Applicable pitch |
| 7382-21 | Ø0.170mm | 0.2mm, 0.25mm, 0.3mm |
| 7382-22 | Ø0.195mm | 0.35mm |
| 7382-23 | Ø0.220mm | 0.4mm |
| 7382-24 | Ø0.250mm | 0.45mm |
| 7382-25 | Ø0 . 290mm | 0.5mm |
| 7382-26 | Ø0.335mm | 0.6mm |
| 7382-27 | Ø0.390mm | 0.7mm |
| 7382-28 | Ø0.455mm | 0.75mm, 0.8mm |
| 7382-29 | Ø0.530mm | 0.9mm |
| 7382-210 | Ø0.620mm | 1.0mm |
| 7382-211 | Ø0.725mm | 1.25mm |
| 7382-212 | Ø0.895mm | 1.5mm |
| 7382-213 | Ø1.100mm | 1.75mm, 2.0mm |
| 7382-214 | Ø1.350mm | 2.5mm |
| 7382-215 | Ø1.650mm | 3.0mm |
| 7382-216 | Ø2.050mm | 3.5mm |
| 7382-217 | Ø2.550mm | 4mm, 4.5mm |
| 7382-218 | Ø3.200mm | 5mm, 5.5mm, 6mm |
| 7382 - 2S | 18 pairs/set, including all above 3-wires | |