


EXPLOSION PROOF ELECTRONIC BALANCES

DATA
OUTPUT

Ex

CUSTOM-MADE

- Suitable for chemical, pharmaceutical, gunpowder, food processing and explosive hazardous occasions
- One-touch calibration
- Counting, percentage display
- LCD display, with backlight
- Unit: g



SPECIFICATION

8105-5KG

Code	8105-500G	8105-1KG	8105-2KG	8105-3KG	8105-5KG
Maximum weighing	500g	1kg	2kg	3kg	5kg
Minimum weighing	0.5g	0.5g	0.5g	0.5g	0.5g
Resolution (d)	0.01g	0.01g	0.01g	0.01g	0.01g
Verification interval (e)	0.1g	0.1g	0.1g	0.1g	0.1g
Accuracy (m is load)	±0.05g	m≤500g: ±0.05g; m>500g: ±0.1g;	m≤500g: ±0.05g; m>500g: ±0.1g;	m≤500g: ±0.05g; 500g<m≤2000g: ±0.1g; m>2000g: ±0.15g	m≤500g: ±0.05g; 500g<m≤2000g: ±0.1g; m>2000g: ±0.15g
Output	RS232				
Operation temperature	15~30°C				
Operation humidity	40%~80% RH				
Stable reading time	≤8s				
Power supply	explosion-proof battery, DC7.4V/4.0Ah				

STANDARD DELIVERY

Main unit	1 pc
Class M1 calibration weight	1 pc
Explosion proof battery	1 pc

OPTIONAL ACCESSORY

RS232 cable (used to connect computers)	8301-CABLE
---	------------



class M1 calibration weight
(included)



explosion proof battery
(included)