

DC POWER SUPPLY CODE 9911-PS305

- Four-digit LED display
- Output power display
- Output switch control
- 10mV/1mA high accuracy and resolution
- Panel locking function to prevent misoperation
- USB interface for power supply
- OVP/OCP protection
- 3 shortcut keys for presetting



test leads (included)

SPECIFICATION

Voltage	Range	30V
	Setting resolution	10mV
	Setting accuracy	≤0.1%+20mV
	Readback resolution	10mV
	Readback accuracy	≤0.1%+20mV
	Load regulation	≤0.1%+5mV
	Line regulation	≤0.01%+5mV
	Ripple	10mVrms
Current	Range	5A
	Setting resolution	1mA
	Setting accuracy	≤0.2%+6mA
	Readback resolution	1mA
	Readback accuracy	≤0.2%+6mA
	Load regulation	≤0.2%+3mA
	Line regulation	≤0.2%+3mA
Ripple	8mArms	
OVP	0~33V	
OCP	0~5.5A	
Work condition	temperature: 0~40°C, humidity: ≤80%RH	
Storage condition	temperature: -20~60°C, humidity: ≤80%RH	
Cool system	fan cool	
Power supply	AC: 220V±10%, 50Hz/60Hz	
Dimension (LxWxH)	230x80x150mm	
Weight	1.45kg	

STANDARD DELIVERY

Main unit	1 pc
Test lead	2 pcs