

INTERNAL TEETH GEAR DOUBLE FLANK MEASURING INSTRUMENT CODE IGE-NF151

- Single-mounting measurement of all errors for the gear under test, including total radial composite deviation (Fi"), single-tooth radial composite deviation (fi"), radial runout (Fr"), center distance deviation (∆a), normal chordal tooth thickness (Wk), and span measurement (M)
- Measurement results are clearly displayed in three colors: red (exceeded), yellow (repairable) and green (qualified)
- Simultaneous display of Cartesian and polar coordinates for quick burr location selection in measurement results, enabling easy localization
- Adjustable measurement speed, automatic separate engagement, controlled air blowing, and configurable rotational direction
- Built-in ISO-1328, JIS-1702, DIN-3983 standards, customer-defined tolerances

SPECIFICATION

SPECIFICATION	
Module range	0.5~8mm
Max. specimen diameter	150mm
Center distance	20~110mm
Micro-motion slide movement range	15mm
Force	10~15N
Measuring the cycle time	2~20s (adjustable)
Indicator system resolution	0.001mm
Variability of indicator reading	0.001mm
Accuracy	0.005mm
Resolution	0.002mm
Air supply	dry and clean, 0.4~0.7MPa
Power supply	220V, 50Hz
Dimension (LxWxH)	690×870×1510mm
Weight	160kg

STANDARD DELIVERY

Main unit	1 pc
Software	1 set
Control cabinet	1 set
Nuts for mounting standard gears	1 set
Standard gear washers	1 set
Standard gear sleeve	1 pc
Axle of small wheel	2 pcs
Base plate	2 pcs

OPTIONAL ACCESSORY

· · · · · · · · · · · · · · · · · · ·	
Standard gear *	IGE-NF-ST

* Requires a drawing of the gear to be measured

