SPECIFICATION

SPECIFICATION		
Optical tube	binocular	
Eyepiece (wide field)	10X (view field: Ø20mm)	
Objective	1X~4.5X (zoom)	
Zoom ratio	1:4.5	
Pupil distance	55~75mm (adjustable)	
Diopter adjustment	±5 diopter (two eyepieces)	
Working distance of objective	97mm	
Max. workpiece height	60mm	
Illumination	adjustable reflected and transmitted LED light	
Power supply	110/220V, 50/60HZ	
Dimension (L×W×H)	260×190×400mm	
Weight	4.3kg	

ZOOM STEREO MICROSCOPE (BASIC TYPE) CODE ISM-ZS30





LED ring light (optional)

STANDARD DELIVERY

Main unit	1 pc
WF 10X eyepiece	2 pcs
Ø95mm glass plate	1 pc
Ø95mm white/black plate	1 pc
Anti-dust cover	1 pc

OPTIONAL ACCESSORY

Auxiliary objective	0.5X	ISM-ZS30-OB05X*
	0.63X	ISM-ZS30-OB06X*
	0.75X	ISM-ZS30-OB07X*
	2X	ISM-ZS30-OB2X
Eyepiece	10X dividing eyepiece (graduation 0.1mm/div.)	ISM-ZS30-EPD10X
	WF15X (view field: Ø16mm)	ISM-ZS50-EP15X
	WF20X (view field: Ø12mm)	ISM-ZS50-EP20X
LED ring lig	ht	ISM-ZS-RL
Sleeve for auxiliary objective		ISM-ZS30-ADAPTER
Digital came	era	ISM-CM63
Camera ada	pter 0.75X **	ISM-AD-0D75

^{*0.5}X, 0.63X and 0.75X auxiliary objectives must be used with ISM-ZS30-ADAPTER

^{**}Digital camera must be used with camera adapter 0.75X