BLUETOOTH DIGITAL TORQUE WRENCHES (KEYBOARD SIGNAL)



TYPE B OPTIONAL ACCURACY: CLOCKWISE: ±1% COUNTER-CLOCKWISE: ±2%

BUILT-IN BLUETOOTH



Torque wrenches:

- Unit: in.lb, ft.lb, N.m, kg.cm
- Clockwise and counter-clockwise operation
- Peak and track working mode
- Can set tolerance with judgement in peak working mode
- 9 target torque values can be set, with audible and visible alarm: LED lights up in sequence, and the buzzer gets louder and louder when torque value is 80%~99.5% of target torque
- Power off in 2 minutes automatically
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

Data transmission:

- Built-in Bluetooth 4.0 module, which can be connected with computers (with Bluetooth function), mobile phones, tablets and other devices
- Keyboard signal, can be transmitted to Excel, Word, TXT
- Transmission distance is 10 meters (no obstacles, no electromagnetic interference)
- Bluetooth connection and disconnection are respectively shown by indicator lights



transmission distance is 10 meters (no obstacles, no electromagnetic interference)

SPECIFICATION

0.1.		IOT 45 MOCA	IOT 45W4OA	IOT 4514/00A	IOT 45MOOA	IOT 45W405A	IOT 4 FINIONS A	IOT 45W040A
Code		IST-15W06A	IST-15W12A	IST-15W20A	IST-15W30A	IST-15W135A	IST-15W200A	IST-15W340A
Туре		A (short handle)			B (long handle)			
Range		1.2~6N.m	2.4~12N.m	4~20N.m	6~30N.m	27~135N.m	40~200N.m	68~340N.m
Accuracy	clockwise	±2%						
	counter-clockwise	±3%						
Tolerance setting range		-20%~+20% (target torque value)						
Resolution		0.001N.m	0.01N.m	0.01N.m	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Square driver (L)		1/4"	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"
Power supply		2xAAA batteries			2xAA batteries			
Length		215mm	215mm	215mm	390mm	415mm	530mm	650mm
Weight		750g	750g	750g	760g	940g	1340g	1540g

OPTIONAL ACCESSORY

	Calibration cable	IST-SD-CABLE
--	-------------------	--------------