

# AC DIGITAL CLAMP METER

## PART NO. 9243-CA600

- Auto/manual ranging
- Maximum mode
- Data hold
- Display backlight
- Work light
- Low battery display
- Auto power off
- Safety rating: CAT III 600V



probes (included)

### SPECIFICATION

Function	Range	Resolution	Accuracy
DC Voltage	200mV/2V/20V/200V	0.1mV/1mV/10mV/0.1V	$\pm(0.8\%+2)$
	600V	1V	$\pm(1.0\%+2)$
AC Voltage	200mV	0.1mV	$\pm(1.0\%+10)$
	2V/20V/200V	1mV/10mV/0.1V	$\pm(1.0\%+5)$
	600V	1V	$\pm(1.2\%+5)$
AC Current	2A( $\leq 0.5A$ )	1mA	$\pm(3.5\%+20)$
	2A	1mA	$\pm(3.0\%+10)$
	20A	10mA	$\pm(3.0\%+10)$
	200A	0.1A	$\pm(2.5\%+10)$
	600A	1A	$\pm(1.5\%+5)$
Resistance	200 $\Omega$ /2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /2M $\Omega$	0.1 $\Omega$ /1 $\Omega$ /10 $\Omega$ /0.1k $\Omega$ /1k $\Omega$	$\pm(1.2\%+2)$
	20M $\Omega$	10k $\Omega$	$\pm(2.0\%+5)$
Diode	open circuit voltage 1.5V		
Continuity buzzer	<50 $\Omega$		
Power supply	3×1.5V AAA batteries		



### STANDARD DELIVERY

Main unit	1 pc
Probe	2 pcs
1.5V battery	3 pcs