

QUALITY INSPECTION TORQUE WRENCH

MEASURE THE TORQUE
OF TIGHTENED BOLT



IST-4W135A

- Measure the torque of tightened bolt with retightening method, read the torque value when the looseness is detected
- Two measuring modes:
 - M1: automatical detecting mode, for normal bolts
 - retighten the bolt, the torque value is displayed on screen when the wrench automatically detects the looseness, both green and red LED light on and buzzer sounds
 - M2: manual detecting mode, for long bolts
 - retighten the bolt, read the torque value when the looseness is detected by hand
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode (only for M2 measuring mode)
- Clockwise and count-clockwise operation
- Memory of 50 results
- Power off in 15 minutes automatically
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

SPECIFICATION

| Part No. | IST-4W30A | IST-4W135A | IST-4W200A | IST-4W340A |
|-------------------|---------------------------------------|----------------|-----------------|-----------------|
| Range | 53.1~265.5in.lb | 239~1195in.lb | 354~1770in.lb | 602~3009in.lb |
| | 4.42~22.12ft.lb | 19.9~99.5ft.lb | 29.5~147.5ft.lb | 50.1~250.7ft.lb |
| Accuracy | clockwise | ±2% | | |
| | counter-clock wise | ±3% | | |
| Resolution | 0.1in.lb | 1in.lb | 1in.lb | 1in.lb |
| | 0.01ft.lb | 0.1ft.lb | 0.1ft.lb | 0.1ft.lb |
| Square driver (L) | 1/4" | 3/8" | 1/2" | 1/2" |
| Power supply | 2xAA batteries, for 110 hours working | | | |
| Length | 15.35" | 16.34" | 20.87" | 25.59" |
| Weight | 1.68lb | 2.07lb | 2.95lb | 3.4lb |

OPTIONAL ACCESSORY

| | |
|-------------------|-------------|
| Calibration cable | IST-W-CABLE |
|-------------------|-------------|