

DIGITAL TORQUE ADAPTER



IST-5W135A

- Clockwise and counter-clockwise operation
- Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque or angle value can be set, with audible and visible alarm: green LED light on and buzzer sounds when torque or angle value is 80%~100% of target torque or angle both green and red LED light on and buzzer sounds when target torque or angle value is reached
- Power off in 2 minutes automatically
- Memory 50 measurement values for browsing
- With overload record (once the torque reaches 110% of the maximum range)



working with ordinary wrench

SPECIFICATION

Part No.		IST-5W30A	IST-5W135A	IST-5W200A	IST-5W340A
Range	torque	53.1~265.5in.lb 4.42~22.12ft.lb	239~1195in.lb 19.9~99.5ft.lb	354~1770in.lb 29.5~147.5ft.lb	602~3009in.lb 50.1~250.7ft.lb
	angle	0 ~ 999°			
Accuracy	clockwise	±3%			
	counter-clock wise	±4%			
	angle	±2° (rotate 90°)			
Resolution	torque	.1in.lb .01ft.lb	1in.lb .1ft.lb	1in.lb .1ft.lb	1in.lb .1ft.lb
	angle	1°			
Square socket and driver		1/4"	3/8"	1/2"	1/2"
Power supply		2xAAA batteries			
Length		3.35"DIA×2.36"	3.35"DIA×2.95"	3.35"DIA×3.15"	3.35"DIA×3.15"
Weight		.33lb	.49lb	.53lb	.53lb

OPTIONAL ACCESSORY

Calibration cable	IST-SD-CABLE
-------------------	--------------