

# DIAL TORQUE WRENCH

ACCURACY:  $\pm 4\%$



IST-DW70

- Clockwise and counter-clockwise operation
- According to DIN ISO 6789, ASME B107.300-2010

## SPECIFICATION

Part No.	IST-DW3D5	IST-DW9	IST-DW18	IST-DW35	IST-DW70	IST-DW140	IST-DW240	IST-DW350
<b>Range</b>	0.7 ~ 3.5N.m 6 ~ 30in.lb	1.8 ~ 9N.m 15 ~ 75in.lb	3.6 ~ 18N.m 30 ~ 150in.lb	7 ~ 35N.m 60 ~ 300in.lb	14 ~ 70N.m 120 ~ 600in.lb	28 ~ 140N.m 20 ~ 100ft.lb	48 ~ 240N.m 35 ~ 175ft.lb	70 ~ 350N.m 50 ~ 250ft.lb
<b>Accuracy</b>	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$
<b>Graduation</b>	0.05N.m 0.5in.lb	0.1N.m 1in.lb	0.2N.m 2in.lb	0.5N.m 5in.lb	1N.m 10in.lb	2N.m 1ft.lb	3N.m 2.5ft.lb	2.5N.m 2.5ft.lb
<b>Square driver (D)</b>	1/4"	1/4"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"
<b>Length</b>	10"	10"	10"	10"	14.88"	21.5"	21.5"	21.5"
<b>Weight</b>	1.06lb	1.06lb	1.06lb	1.06lb	1.82lb	2.89lb	2.89lb	2.89lb