

SMALL RANGE DIGITAL TORQUE WRENCH



IST-WP20

SPECIFICATION

Part No.	IST-WP6	IST-WP12	IST-WP20
Range	10.6~53.09in.lb	21.2~106.2in.lb	35.4~177.0in.lb
	0.884~4.424ft.lb	1.77~8.85ft.lb	2.95~14.75ft.lb
Accuracy	clockwise ±3%	±3%	±3%
	counter-clockwise ±4%	±4%	±4%
Resolution	0.01in.lb	0.1in.lb	0.1in.lb
	0.001ft.lb	0.01ft.lb	0.01ft.lb
Square driver (L)	1/4"	1/4"	1/4"
Power supply	1×AAA battery		
Length	10.24"	10.24"	10.24"
Weight	0.95lb	0.95lb	0.95lb

- Clockwise and counter-clockwise operation
- Unit: in.lb, ft.lb, N.m, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when target torque value is 90%~100% of target torque
 - Red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

OPTIONAL ACCESSORY

Calibration cable

IST-SD-CABLE