

AUTOMATIC ROCKWELL HARDNESS TESTER CODE ISH-MR150**

SPECIFICATION

Hardness scale	HRA, HRB, HRC, HRD, HRF, HRG
Preliminary test force	98N
Test force	588N, 980N, 1471N
Display	analogue
Stage elevation	manual
Load control	automatic (load/dwell/unload)
Load dwell time	1~99 second
Min. reading	0.5HR
Max. workpiece height	170mm
Max. workpiece depth	165mm (from the center of indenter)
Power supply	220V, 50/60Hz**
Dimension	520×160×700mm
Weight	60kg



Ø60mm flat anvil
(included)



small V-type anvil (optional)
for cylinders with diameter
Ø2 ~ 4mm



Ø150mm flat anvil
(included)



V-type anvil (included)
for cylinders with diameter
Ø4 ~ 60mm



STANDARD DELIVERY

Main unit	1pc
Ø60mm flat anvil	1pc
Ø150mm flat anvil	1pc
V-type anvil	1pc
Diamond indenter	1pc
Ø1.5875mm carbide ball indenter	1pc
Hardness test block HRB88~95	1pc
Hardness test block HRC60~65	1pc

STANDARD DELIVERY

Hardness test block HRC20~30	1pc
Anti-dust cover	1pc

OPTIONAL ACCESSORY

Hardness test block HRB88~95	ISH-BHRB
Hardness test block HRC60~65	ISH-BHRC3
Hardness test block HRC20~30	ISH-BHRC1
Small V-type anvil	ISH-SMALL ANVIL

** Add "-U" on code No. when power supply is 110V, 50/60Hz

