

DIAL TORQUE WRENCH

ACCURACY: $\pm 4\%$



IST-DW70

- Clockwise and counter-clockwise operation
- According to DIN ISO 6789, ASME B107.300-2010

SPECIFICATION

Code	IST-DW3D5	IST-DW9	IST-DW18	IST-DW35	IST-DW70	IST-DW140	IST-DW240	IST-DW350
Range	0.7 ~ 3.5N.m 6 ~ 30in.lb	1.8 ~ 9N.m 15 ~ 75in.lb	3.6 ~ 18N.m 30 ~ 150in.lb	7 ~ 35N.m 60 ~ 300in.lb	14 ~ 70N.m 120 ~ 600in.lb	28 ~ 140N.m 20 ~ 100ft.lb	48 ~ 240N.m 35 ~ 175ft.lb	70 ~ 350N.m 50 ~ 250ft.lb
Accuracy	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$	$\pm 4\%$
Graduation	0.05N.m 0.5in.lb	0.1N.m 1in.lb	0.2N.m 2in.lb	0.5N.m 5in.lb	1N.m 10in.lb	2N.m 1ft.lb	3N.m 2.5ft.lb	2.5N.m 2.5ft.lb
Square driver (D)	1/4"	1/4"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"
Length	254mm	254mm	254mm	254mm	378mm	546mm	546mm	546mm
Weight	480g	480g	480g	480g	820g	1300g	1300g	1300g