

- Graduation 0.001mm
- Carbide measuring faces
- Meet DIN863-1
- Supplied with setting standards (except 0-25mm)

**Ratchet stop type (mm)**

Code	Range	Accuracy	L	a	b
<b>3210-25A*</b>	0-25mm	4µm	32	9	28
<b>3210-50A*</b>	25-50mm	4µm	57	14	38
<b>3210-75A*</b>	50-75mm	5µm	82	15	49
<b>3210-100A*</b>	75-100mm	5µm	107	15	60
<b>3210-125A</b>	100-125mm	6µm	133	16.5	73
<b>3210-150A</b>	125-150mm	6µm	158	16.5	85
<b>3210-175A</b>	150-175mm	7µm	183	19.4	104
<b>3210-200A</b>	175-200mm	7µm	209	19.4	117


**Friction thimble type (mm)**

Code	Range	Accuracy	L	a	b
<b>3210-25FA*</b>	0-25mm	4µm	32	9	28
<b>3210-50FA*</b>	25-50mm	4µm	57	14	38

## 1µm GRADUATION OUTSIDE MICROMETERS



**3210-25A**



**Micrometer set (ratchet stop type)**

Code	Range	Micrometers included
<b>3210-753A*</b>	0-75mm	3210-25A, 3210-50A, 3210-75A
<b>3210-1004A*</b>	0-100mm	3210-25A, 3210-50A, 3210-75A, 3210-100A
<b>3210-1506A</b>	0-150mm	3210-25A, 3210-50A, 3210-75A, 3210-100A, 3210-125A, 3210-150A

\*Supplied with manufacturer inspection certificate traceable to DKD Germany